

Pin assignment

Pin assignment number: 10299

Index:

09.07.2014

Connector name: 12-pol CONTACT

Pin-count: 12

Page: 1/1

Pin	Designation	Description	Level	Driver	NC	Colour
1	Ground IN	Ground	0V			white
2	Supply Voltage IN	Supply voltage	11-27V			brown
3	SSI_Clock+_IN	Clock input +	RS 422	RS 422		green
4	SSI_Clock-_IN	Clock input -	RS 422	RS 422		yellow
5	SSI_DATA+_OUT	Data output +	RS 422	RS 422		gray
6	SSI_DATA-_OUT	Data output -	RS 422	RS 422		pink
7	Preset1 IN_1	Preset1 IN_1	Supply Voltage		0	blue
8	Direction IN	Change of counting direction	Supply Voltage		0	red
9	not connected					
10	Ser.Program+_IN/OUT	Ser. programming interface RS485	RS 485	RS 485		violet
11	Ser.Program-_IN/OUT	Ser. programming interface RS485	RS 485	RS 485		gray/pink
12	not connected					

WARNING

'De-energize the system before carrying out wiring work or opening and closing electrical connections !

Short-circuits, voltage peaks, etc. can cause operating failures and uncontrolled operating states, as well as serious personal injuries and damage to property.

Verdrahtungsarbeiten, Öffnen und Schließen von elektrischen Verbindungen nur im spannungslosen Zustand durchführen ! Kurzschlüsse, Spannungsspitzen etc. können zur Fehlfunktion und unkontrollierten Zuständen der Anlage bzw. zu erheblichen Personen- und Sachschäden führen.