

Pin assignment

Pin assignment number: 1065

Connector name: 25-pol SUB-D

Index:

Pin-count: 25

13.01.2021

Page: 1/1

Pin	Designation	Description	Colour
1	DATA+_OUT	Data output +	-
2	DATA-_OUT	Data output -	-
3	Adress 2^0_IN	Encoder address 2^0	-
4	Adress 2^1_IN	Encoder address 2^1	-
5	Adress 2^2_IN	Encoder address 2^2	-
6	Adress 2^3_IN	Encoder address 2^3	-
7	D+ 120 Ohm		-
8	Preset1_IN	Preset value 1	-
9	Screen	Shield	-
10	not connected		-
11	not connected		-
12	not connected		-
13	not connected		-
14	not connected		-
15	not connected		-
16	not connected		-
17	not connected		-
18	not connected		-
19	not connected		-
20	not connected		-
21	not connected		-
22	not connected		-
23	not connected		-
24	Supply Voltage IN	Supply voltage	-
25	Ground IN	Ground	-

D+ 120 Ohm :

'With a bridge from Data - to D+120 ohm, a terminating resistor of 120 ohm is connected !

WARNING

'De-energize the system before carrying out wiring work or opening and closing electrical connections !

Short-circuits, voltage peaks, etc. can cause operating failures and uncontrolled operating states, as well as serious personal injuries and damage to property.

Verdrahtungsarbeiten, Öffnen und Schließen von elektrischen Verbindungen nur im spannungslosen Zustand durchführen ! Kurzschlüsse, Spannungsspitzen etc. können zur Fehlfunktion und unkontrollierten Zuständen der Anlage bzw. zu erheblichen Personen- und Sachschäden führen.