

Pin assignment

Pin assignment number: 11175

Connector name: M23 12-pol with cable

Index:

Pin-count: 12

25.01.2021

Page: 1/1

| Pin | Designation | Description | Colour |
|-----|-------------------|----------------------------|-------------|
| 1 | Ground IN | Ground | white/green |
| 2 | Supply Voltage IN | Supply voltage | brown/green |
| 3 | CH_A_OUT | Channel A | brown |
| 4 | CH_B_OUT | Channel B | gray |
| 5 | CH_I_OUT | Channel Reference | red |
| 6 | /CH_A_OUT | Channel A inverted | green |
| 7 | /CH_B_OUT | Channel B inverted | pink |
| 8 | /CH_I_OUT | Channel Reference inverted | black |
| 9 | not connected | | |
| 10 | not connected | | |
| 11 | not connected | | |
| 12 | not connected | | |

! SHIELD !

'transparency

,

Shield

'Shield over connector housing

Schirm über Steckergehäuse

,

WARNING

'De-energize the system before carrying out wiring work or opening and closing electrical connections !

Short-circuits, voltage peaks, etc. can cause operating failures and uncontrolled operating states, as well as serious personal injuries and damage to property.

Verdrahtungsarbeiten, Öffnen und Schließen von elektrischen Verbindungen nur im spannungslosen Zustand durchführen ! Kurzschlüsse, Spannungsspitzen etc. können zur Fehlfunktion und unkontrollierten Zuständen der Anlage bzw. zu erheblichen Personen- und Sachschäden führen.

,