

## Pin assignment

Pin assignment number: 11197

Index:

26.01.2021

Connector name: M23 12-pol

Pin-count: 12

Page: 1/1

Pin	Designation	Description	Level	Driver	NC	Colour
1	CH_A_OUT	Channel A	5V	RS 422		-
2	/CH_A_OUT	Channel A inverted	5V	RS 422		-
3	not connected					-
4	CH_B_OUT	Channel B	5V	RS 422		-
5	/CH_B_OUT	Channel B inverted	5V	RS 422		-
6	not connected					-
7	CH_I_OUT	Channel Reference	5V	RS 422		-
8	/CH_I_OUT	Channel Reference inverted	5V	RS 422		-
9	not connected					-
10	not connected					-
11	Supply Voltage IN	Supply voltage	11-28V			-
12	Ground IN	Ground	0V			-

### Connector coding

'! connector+20°coded

### WARNING

'De-energize the system before carrying out wiring work or opening and closing electrical connections !

Short-circuits, voltage peaks, etc. can cause operating failures and uncontrolled operating states, as well as serious personal injuries and damage to property.

Verdrahtungsarbeiten, Öffnen und Schließen von elektrischen Verbindungen nur im spannungslosen Zustand durchführen ! Kurzschlüsse, Spannungsspitzen etc. können zur Fehlfunktion und unkontrollierten Zuständen der Anlage bzw. zu erheblichen Personen- und Sachschäden führen.