

Pin assignment

Pin assignment number: 1371

Index: A

13.01.2021

Connector name: 32-pol CANNON

Pin-count: 32

Page: 1/1

Pin	Designation	Description	Colour
A	O_D0	Data output	-
B	O_D1	Data output	-
C	O_D2	Data output	-
D	O_D3	Data output	-
E	O_D4	Data output	-
F	O_D5	Data output	-
G	O_D6	Data output	-
H	O_D7	Data output	-
J	O_D8	Data output	-
K	O_D9	Data output	-
L	O_D10	Data output	-
M	O_D11	Data output	-
N	O_D12	Data output	-
P	O_D13	Data output	-
R	O_D14	Data output	-
S	O_D15	Data output	-
T	O_D16	Data output	-
U	O_D17	Data output	-
V	not connected		-
W	not connected		-
X	Direction IN	Counting direction increasing	-
Y	Preset1_IN	Preset value 1	-
Z	not connected		-
a	Supply Voltage IN	Supply voltage	-
b	Ground IN	Ground	-
c	Ser.Program+_IN/OUT	Ser. programming interface RS485	-
d	Ser.Program-_IN/OUT	Ser. programming interface RS485	-
e	not connected		-
f	not connected		-
g	not connected		-
h	not connected		-
i	not connected		-