

Pin assignment

Pin assignment number: 155

Connector name: 15-pol HARTING

Index:

Pin-count: 15

13.01.2021

Page: 1/1

| Pin | Designation | Description | Colour |
|-----|---------------------------|--------------------------------|--------|
| A1 | Adress 2 ⁰ _IN | Encoder address 2 ⁰ | - |
| A2 | Adress 2 ¹ _IN | Encoder address 2 ¹ | - |
| A3 | Adress 2 ² _IN | Encoder address 2 ² | - |
| A4 | Adress 2 ³ _IN | Encoder address 2 ³ | - |
| A5 | not connected | | - |
| B1 | Clock+_IN | Clock input + | - |
| B2 | Clock-_IN | Clock input - | - |
| B3 | DATA+_OUT | Data output + | - |
| B4 | DATA-_OUT | Data output - | - |
| B5 | not connected | | - |
| C1 | Format recognition | | - |
| C2 | not connected | | - |
| C3 | not connected | | - |
| C4 | Supply Voltage IN | Supply voltage | - |
| C5 | Ground IN | Ground | - |

FORMAT DETECTION: 'LOW = TA-MINI

HIGH = PT-100

WARNING

'De-energize the system before carrying out wiring work or opening and closing electrical connections !

Short-circuits, voltage peaks, etc. can cause operating failures and uncontrolled operating states, as well as serious personal injuries and damage to property.

Verdrahtungsarbeiten, Öffnen und Schließen von elektrischen Verbindungen nur im spannungslosen Zustand durchführen ! Kurzschlüsse, Spannungsspitzen etc. können zur Fehlfunktion und unkontrollierten Zuständen der Anlage bzw. zu erheblichen Personen- und Sachschäden führen.