

Pin assignment

Pin assignment number: 159

Connector name: 25-pol SUB-D

Index:

Pin-count: 25

13.01.2021

Page: 1/1

Pin	Designation	Description	Colour
1	O_D0	Data output	-
2	O_D1	Data output	-
3	O_D2	Data output	-
4	O_D3	Data output	-
5	O_D4	Data output	-
6	O_D5	Data output	-
7	O_D5 neg.	Data output inverted	-
8	not connected		-
9	not connected		-
10	not connected		-
11	not connected		-
12	not connected		-
13	not connected		-
14	not connected		-
15	not connected		-
16	not connected		-
17	not connected		-
18	not connected		-
19	not connected		-
20	not connected		-
21	not connected		-
22	not connected		-
23	not connected		-
24	Supply Voltage IN	Supply voltage	-
25	Ground IN	Ground	-

CHANGE OF COUNTING DIRECT

'D0 to D4 and D5 =====> Value increasing

D0 to D4 and D5neg. =====> Value decreasing
(Shaft rotational clockwise)

WARNING

'De-energize the system before carrying out wiring work or opening and closing electrical connections !

Short-circuits, voltage peaks, etc. can cause operating failures and uncontrolled operating states, as well as serious personal injuries and damage to property.

Verdrahtungsarbeiten, Öffnen und Schließen von elektrischen Verbindungen nur im spannungslosen Zustand durchführen ! Kurzschlüsse, Spannungsspitzen etc. können zur Fehlfunktion und unkontrollierten Zuständen der Anlage bzw. zu erheblichen Personen- und Sachschäden führen.