

# Pin assignment

Pin assignment number: 1650

Connector name: M23 12-pol

Index:

Pin-count: 12

13.01.2021

Page: 1/1

| Pin | Designation               | Description                    | Colour |
|-----|---------------------------|--------------------------------|--------|
| 1   | PNT_Adress+_IN            | Data input +                   | -      |
| 2   | PNT_Adress-_IN            | Data input -                   | -      |
| 3   | PNT_Data+_OUT             | Data output +                  | -      |
| 4   | PNT_Data-_OUT             | Data output -                  | -      |
| 5   | Baud 2 <sup>0</sup> _IN   | Baud rate 2 <sup>0</sup>       | -      |
| 6   | Baud 2 <sup>1</sup> _IN   | Baud rate 2 <sup>1</sup>       | -      |
| 7   | Adress 2 <sup>0</sup> _IN | Encoder address 2 <sup>0</sup> | -      |
| 8   | Adress 2 <sup>1</sup> _IN | Encoder address 2 <sup>1</sup> | -      |
| 9   | Adress 2 <sup>2</sup> _IN | Encoder address 2 <sup>2</sup> | -      |
| 10  | Preset1_IN                | Preset value 1                 | -      |
| 11  | Supply Voltage IN         | Supply voltage                 | -      |
| 12  | Ground IN                 | Ground                         | -      |

| BAUD RATE : | '                | 307200 | 38400 | 19200 | 9600 |
|-------------|------------------|--------|-------|-------|------|
|             | 2 <sup>0</sup> : | NC     | US    | NC    | US   |
|             | 2 <sup>1</sup> : | NC     | NC    | US    | US   |
|             | 2 <sup>2</sup> : | NC     | NC    | NC    | NC   |
|             | 2 <sup>3</sup> : | NC     | NC    | NC    | NC   |
|             | '                |        |       |       |      |