

Pin assignment

Pin assignment number: 1744

Connector name: 25-pol SUB-D

Index:

Pin-count: 25

13.01.2021

Page: 1/2

Pin	Designation	Description	Colour
1	CAN H	Data output	-
2	CAN L	Data output	-
3	not connected		-
4	not connected		-
5	A0		-
6	A1		-
7	A2		-
8	A3		-
9	A4		-
10	A5		-
11	A6		-
12	A7		-
13	not connected		-
14	not connected		-
15	not connected		-
16	not connected		-
17	not connected		-
18	not connected		-
19	not connected		-
20	not connected		-
21	not connected		-
22	not connected		-
23	not connected		-
24	Supply Voltage IN	Supply voltage	-
25	Ground IN	Ground	-

Address coding :

'A7	A6	A5	A4	A3	A2	A1	A0	Address
X	X	X	X	X	X	X	X	0
X	X	X	X	X	X	X	0	1
X	X	X	X	X	X	0	X	2
X	X	X	X	X	X	0	0	3
.
.
0	0	0	0	0	0	0	0	255

X = Unconnected
0 = Connected with 0 Volt = Ground

Pin assignment

Pin assignment number: 1744

Connector name: 25-pol SUB-D

Index:

Pin-count: 25

13.01.2021

Page: 2/2

WARNING

'De-energize the system before carrying out wiring work or opening and closing electrical connections !

Short-circuits, voltage peaks, etc. can cause operating failures and uncontrolled operating states, as well as serious personal injuries and damage to property.

Verdrahtungsarbeiten, Öffnen und Schließen von elektrischen Verbindungen nur im spannungslosen Zustand durchführen ! Kurzschlüsse, Spannungsspitzen etc. können zur Fehlfunktion und unkontrollierten Zuständen der Anlage bzw. zu erheblichen Personen- und Sachschäden führen.