

Pin assignment

Pin assignment number: 1794

Connector name: with cable outlet

Index:

Pin-count: 25

13.01.2021

Page: 1/1

Pin	Designation	Description	Colour
1	PNT_Adress+_IN	Data input +	white
2	PNT_Adress-_IN	Data input -	brown
3	PNT_Data+_OUT	Data output +	green
4	PNT_Data-_OUT	Data output -	yellow
5	Adress 2 ³ _IN	Encoder address 2 ³	gray
6	Baud 2 ⁰ _IN	Baud rate 2 ⁰	pink
7	Baud 2 ¹ _IN	Baud rate 2 ¹	blue
8	Adress 2 ¹ _IN	Encoder address 2 ¹	red
9	Adress 2 ² _IN	Encoder address 2 ²	black
10	Preset1_IN	Preset value 1	violet
11	Preset2_IN	Preset value 2	gray/pink
12	Adress 2 ⁰ _IN	Encoder address 2 ⁰	red/blue
13	not connected		
14	not connected		
15	not connected		
16	not connected		
17	not connected		
18	not connected		
19	not connected		
20	not connected		
21	not connected		
22	not connected		
23	not connected		
24	Supply Voltage IN	Supply voltage	brown/red
25	Ground IN	Ground	white/black

BAUD RATE :	'	307200	38400	19200	9600
2 ⁰ :	NC	US	NC	US	
2 ¹ :	NC	NC	US	US	
2 ² :	NC	NC	NC	NC	
2 ³ :	NC	NC	NC	NC	
'					

WARNING

'De-energize the system before carrying out wiring work or opening and closing electrical connections !

Short-circuits, voltage peaks, etc. can cause operating failures and uncontrolled operating states, as well as serious personal injuries and damage to property.

Verdrahtungsarbeiten, Öffnen und Schließen von elektrischen Verbindungen nur im spannungslosen Zustand durchführen ! Kurzschlüsse, Spannungsspitzen etc. können zur Fehlfunktion und unkontrollierten Zuständen der Anlage bzw. zu erheblichen Personen- und Sachschäden führen.