

## Pin assignment

Pin assignment number: 1824

Connector name: M23 12-pol

Index:

Pin-count: 12

13.01.2021

Page: 1/1

Pin	Designation	Description	Colour
1	TXD-	Data output -	-
2	TXD+	Data output +	-
3	RXD+	Clock input +	-
4	RXD-	Clock input -	-
5	Direction IN	Change of counting direction	-
6	Preset1_IN	Preset value 1	-
7	Binär-Input A		-
8	Binär-Input B		-
9	Adress 2 <sup>0</sup> _IN	Encoder address 2 <sup>0</sup>	-
10	Adress 2 <sup>1</sup> _IN	Encoder address 2 <sup>1</sup>	-
11	Supply Voltage IN	Supply voltage	-
12	Ground IN	Ground	-

### WARNING

'De-energize the system before carrying out wiring work or opening and closing electrical connections !

Short-circuits, voltage peaks, etc. can cause operating failures and uncontrolled operating states, as well as serious personal injuries and damage to property.

Verdrahtungsarbeiten, Öffnen und Schließen von elektrischen Verbindungen nur im spannungslosen Zustand durchführen ! Kurzschlüsse, Spannungsspitzen etc. können zur Fehlfunktion und unkontrollierten Zuständen der Anlage bzw. zu erheblichen Personen- und Sachschäden führen.