

Pin assignment

Pin assignment number: 1869

Index:

13.01.2021

Connector name: with cable outlet

Pin-count: 16

Page: 1/1

Pin	Designation	Description	Colour
1	SSI_DATA+_OUT	Data output +	white
2	SSI_DATA-_OUT	Data output -	brown
3	SSI_Clock+_IN	Clock input +	green
4	SSI_Clock-_IN	Clock input -	yellow
5	Softendswitch_OUT	Data output	gray
6	Softendswitch_OUT	Data output	pink
7	Softendswitch_OUT	Data output	blue
8	Softendswitch_OUT	Data output	red
9	Softendswitch_OUT	Data output	black
10	Softendswitch_OUT	Data output	violet
11	Softendswitch_OUT	Data output	gray/pink
12	Softendswitch_OUT	Data output	red/blue
13	Ser.Program+_IN/OUT	Ser. programming interface RS485	white/green
14	Ser.Program-_IN/OUT	Ser. programming interface RS485	brown/green
15	Supply Voltage IN	Supply voltage	white/yellow
16	Ground IN	Ground	yellow/brown

WARNING

'De-energize the system before carrying out wiring work or opening and closing electrical connections !

Short-circuits, voltage peaks, etc. can cause operating failures and uncontrolled operating states, as well as serious personal injuries and damage to property.

Verdrahtungsarbeiten, Öffnen und Schließen von elektrischen Verbindungen nur im spannungslosen Zustand durchführen ! Kurzschlüsse, Spannungsspitzen etc. können zur Fehlfunktion und unkontrollierten Zuständen der Anlage bzw. zu erheblichen Personen- und Sachschäden führen.