

Pin assignment

Pin assignment number: 1949

Index:

13.01.2021

Connector name: 25-pol SUB-D

Pin-count: 25

Page: 1/1

Pin	Designation	Description	Colour
1	O_D0	Data output	-
2	O_D1	Data output	-
3	O_D2	Data output	-
4	not connected		-
5	Inpos. 2 Degree (E10)		-
6	not connected		-
7	Rapid traverse		-
8	not connected		-
9	Creep speed		-
10	not connected		-
11	not connected		-
12	not connected		-
13	Input P		-
14	not connected		-
15	Output 9 Grad		-
16	Output 12 Grad		-
17	Output 15 Grad		-
18	Output 43 Grad		-
19	not connected		-
20	not connected		-
21	Direction IN	Change of counting direction	-
22	Input A1.1		-
23	not connected		-
24	Supply Voltage IN	Supply voltage	-
25	Ground IN	Ground	-

Input P : 'With connection of the input with 9 degree, or 12 degree etc. , the

Quick-Traverse and Creep-Motion can be changed.

Input A1.1 : 'High (11-27 V) = Quick-Traverse + Creep-Motion active !

WARNING

'De-energize the system before carrying out wiring work or opening and closing electrical connections !
Short-circuits, voltage peaks, etc. can cause operating failures and uncontrolled operating states, as well as serious personal injuries and damage to property.

Verdrahtungsarbeiten, Öffnen und Schließen von elektrischen Verbindungen nur im spannungslosen Zustand durchführen ! Kurzschlüsse, Spannungsspitzen etc. können zur Fehlfunktion und unkontrollierten Zuständen der Anlage bzw. zu erheblichen Personen- und Sachschäden führen.