

Pin assignment

Pin assignment number: 2467

Index: A

13.01.2021

Connector name: with cable outlet

Pin-count: 25

Page: 1/1

Pin	Designation	Description	Colour
1	O_D0	Data output	white
2	O_D1	Data output	brown
3	O_D2	Data output	green
4	O_D3	Data output	yellow
5	O_D4	Data output	gray
6	O_D5	Data output	pink
7	O_D6	Data output	blue
8	O_D7	Data output	red
9	O_D8	Data output	black
10	O_D9	Data output	violet
11	O_D10	Data output	gray/pink
12	O_D11	Data output	red/blue
13	O_D12	Data output	white/green
14	not connected		
15	not connected		
16	not connected		
17	Fault_OUT	HIGH=DATA VALID	brown/red
18	Preset1_IN	Preset value 1	yellow/blue
19	I_Latch	High=Latch	brown/black
20	Direction IN	Change of counting direction	white/black
21	Preset2_IN	Change of counting direction	green/blue
22	Ser.Program+_IN/OUT	Ser. programming interface RS485	yellow/gray
23	Ser.Program-_IN/OUT	Ser. programming interface RS485	pink/green
24	Supply Voltage IN	Supply voltage	yellow/pink
25	Ground IN	Ground	gray/green

WARNING

'De-energize the system before carrying out wiring work or opening and closing electrical connections !

Short-circuits, voltage peaks, etc. can cause operating failures and uncontrolled operating states, as well as serious personal injuries and damage to property.

Verdrahtungsarbeiten, Öffnen und Schließen von elektrischen Verbindungen nur im spannungslosen Zustand durchführen ! Kurzschlüsse, Spannungsspitzen etc. können zur Fehlfunktion und unkontrollierten Zuständen der Anlage bzw. zu erheblichen Personen- und Sachschäden führen.