

## Pin assignment

Pin assignment number: 2473

Index:

13.01.2021

Connector name: 26-pol CONTACT

Pin-count: 26

Page: 1/1

Pin	Designation	Description	Colour
1	O_D0	Data output	-
2	O_D1	Data output	-
3	O_D2	Data output	-
4	O_D3	Data output	-
5	O_D4	Data output	-
6	O_D5	Data output	-
7	O_D6	Data output	-
8	O_D7	Data output	-
9	O_D8	Data output	-
10	O_D9	Data output	-
11	O_D10	Data output	-
12	O_D11	Data output	-
13	O_D12	Data output	-
14	Softendswitch_OUT	Data output	-
15	Softendswitch_OUT	Data output	-
16	Softendswitch_OUT	Data output	-
17	Softendswitch_OUT	Data output	-
18	Softendswitch_OUT	Data output	-
19	Preset1_IN	Preset value 1	-
20	Preset2_IN	Preset value 2	-
21	Direction IN	Change of counting direction	-
22	Ser.Program+_IN/OUT	Ser. programming interface RS485	-
23	Ser.Program-_IN/OUT	Ser. programming interface RS485	-
24	Supply Voltage IN	Supply voltage	-
25	Ground IN	Ground	-
26	I_Latch	High=Latch	-