

Pin assignment

Pin assignment number: 2530

Index:

13.01.2021

Connector name: with cable outlet

Pin-count: 24

Page: 1/1

Pin	Designation	Description	Colour
1	O_D0	Data output	white
2	O_D1	Data output	brown
3	O_D2	Data output	green
4	O_D3	Data output	yellow
5	O_D4	Data output	gray
6	O_D5	Data output	pink
7	O_D6	Data output	black
8	O_D7	Data output	violet
9	O_D8	Data output	gray/pink
10	O_D9	Data output	red/blue
11	O_D10	Data output	white/green
12	O_D11	Data output	brown/green
13	O_D12	Data output	gray/brown
14	O_D13	Data output	white/pink
15	O_D14	Data output	pink/brown
16	O_D15	Data output	white/blue
17	Parity dynamically	Parity Even	yellow/brown
18	Parity static	Static HIGH	white/gray
19	I_Latch	High=Latch	white/red
20	Direction IN	Counting direction increasing	white/yellow
21	Ser.Program+_IN/OUT	Ser. programming interface RS485	brown/red
22	Ser.Program-_IN/OUT	Ser. programming interface RS485	brown/blue
23	Supply Voltage IN	Supply voltage	red
24	Ground IN	Ground	blue