

Pin assignment

Pin assignment number: 2720

Connector name: 26-pol CONTACT

Index:

Pin-count: 26

13.01.2021

Page: 1/1

Pin	Designation	Description	Colour
1	SSI_Clock-_IN	Clock input -	-
2	SSI_Clock+_IN	Clock input +	-
3	SSIDT+/Ser.Pr.+	Data+/Prog.-Input+	-
4	SSIDT-/Ser.Pr.-	Data-/Prog.-Input-	-
5	CH_A_OUT	Channel A	-
6	/CH_A_OUT	Channel A inverted	-
7	CH_B_OUT	Channel B	-
8	/CH_B_OUT	Channel B inverted	-
9	CH_I_OUT	Channel Reference	-
10	/CH_I_OUT	Channel Reference inverted	-
11	not connected		-
12	not connected		-
13	not connected		-
14	not connected		-
15	not connected		-
16	not connected		-
17	not connected		-
18	not connected		-
19	not connected		-
20	Preset1_IN	Preset value 1	-
21	Direction IN	Counting direction increasing	-
22	not connected		-
23	not connected		-
24	Supply Voltage IN	Supply voltage	-
25	Ground IN	Ground	-
26	not connected		-

ZE-Programming note : 'If the encoder is programmed, no signal must be connected at SSI_Clock -_IN and SSI_Clock+_IN !