

## Pin assignment

Pin assignment number: 2730

Index:

13.01.2021

Connector name: 25-pol SUB-D

Pin-count: 25

Page: 1/1

Pin	Designation	Description	Colour
1	SSI_Clock-_IN	Clock input -	-
2	SSI_Clock+_IN	Clock input +	-
3	SSI_DATA+_OUT	Data output +	-
4	SSI_DATA-_OUT	Data output -	-
5	Ser.Program+_IN/OUT	Ser. programming interface RS485	-
6	Ser.Program-_IN/OUT	Ser. programming interface RS485	-
7	not connected		-
8	CH_A_OUT	Channel A	-
9	/CH_A_OUT	Channel A inverted	-
10	CH_B_OUT	Channel B	-
11	/CH_B_OUT	Channel B inverted	-
12	Limit switch_OUT	Output	-
13	Limit switch_OUT	Output	-
14	Limit switch_OUT	Output	-
15	Limit switch_OUT	Output	-
16	Limit switch_OUT	Output	-
17	Limit switch_OUT	Output	-
18	Limit switch_OUT	Output	-
19	Limit switch_OUT	Output	-
20	Preset1_IN	for SSI output	-
21	Preset2_IN	for SSI output	-
22	Preset3_IN	for drum position	-
23	not connected		-
24	Supply Voltage IN	Supply voltage	-
25	Ground IN	Ground	-