

Pin assignment

Pin assignment number: 3029

Index:

13.01.2021

Connector name: with cable outlet

Pin-count: 12

Page: 1/1

Pin	Designation	Description	Colour
1	SSI_Clock-_IN	Clock input -	white
2	SSI_Clock+_IN	Clock input +	brown
3	SSI_DATA+_OUT	Data output +	green
4	SSI_DATA-_OUT	Data output -	yellow
5	Analog +	Prog.: 0-10V,0-20mA,4-20mA	gray
6	Analog -	Prog.: 0-10V,0-20mA,4-20mA	pink
7	Ser.Program-_IN/OUT	Ser. programming interface RS485	blue
8	Progr.-Input	(Latch-Analog)	red
9	Progr.-Input	(Preset1)	black
10	Ser.Program+_IN/OUT	Ser. programming interface RS485	violet
11	Supply Voltage IN	Supply voltage	gray/pink
12	Ground IN	Ground	red/blue

WARNING

'De-energize the system before carrying out wiring work or opening and closing electrical connections !

Short-circuits, voltage peaks, etc. can cause operating failures and uncontrolled operating states, as well as serious personal injuries and damage to property.

Verdrahtungsarbeiten, Öffnen und Schließen von elektrischen Verbindungen nur im spannungslosen Zustand durchführen ! Kurzschlüsse, Spannungsspitzen etc. können zur Fehlfunktion und unkontrollierten Zuständen der Anlage bzw. zu erheblichen Personen- und Sachschäden führen.