

Pin assignment

Pin assignment number: 3182

Index:

13.01.2021

Connector name: with cable outlet

Pin-count: 18

Page: 1/1

Pin	Designation	Description	Colour
1	SSI_Clock-_IN 1	Clock input -	white
2	SSI_Clock+_IN 1	Clock input +	brown
3	SSI_DATA+_OUT 1	Data output +	green
4	SSI_DATA-_OUT 1	Data output -	yellow
5	not connected		
6	not connected		
7	SSI_Clock-_IN 2	Clock input -	blue
8	SSI_Clock+_IN 2	Clock input +	red
9	SSI_DATA+_OUT 2	Data output +	black
10	SSI_DATA-_OUT 2	Data output -	violet
11	not connected		
12	Ser.Program+_IN/OUT	Ser. programming interface RS485	red/blue
13	Ser.Program-_IN/OUT	Ser. programming interface RS485	white/green
14	Direction IN	Change of counting direction	brown/green
15	Preset1_IN	Preset value 1	white/yellow
16	Preset2_IN	Preset value 2	yellow/brown
17	Supply Voltage IN	Supply voltage	white/gray
18	Ground IN	Ground	gray/brown

WARNING

'De-energize the system before carrying out wiring work or opening and closing electrical connections !

Short-circuits, voltage peaks, etc. can cause operating failures and uncontrolled operating states, as well as serious personal injuries and damage to property.

Verdrahtungsarbeiten, Öffnen und Schließen von elektrischen Verbindungen nur im spannungslosen Zustand durchführen ! Kurzschlüsse, Spannungsspitzen etc. können zur Fehlfunktion und unkontrollierten Zuständen der Anlage bzw. zu erheblichen Personen- und Sachschäden führen.