

Pin assignment

Pin assignment number: 3288

Index:

13.01.2021

Connector name: with cable outlet

Pin-count: 25

Page: 1/1

Pin	Designation	Description	Colour
1	O_D0	Data output	white
2	O_D1	Data output	brown
3	O_D2	Data output	green
4	O_D3	Data output	yellow
5	O_D4	Data output	gray
6	O_D5	Data output	pink
7	O_D6	Data output	blue
8	O_D7	Data output	red
9	O_D8	Data output	black
10	O_D9	Data output	violet
11	O_D10	Data output	gray/pink
12	O_D11	Data output	red/blue
13	CH_A_OUT	Channel A	white/green
14	CH_B_OUT	Channel B	brown/green
15	not connected		
16	Softendswitch_OUT1	Cam 1	yellow/brown
17	not connected		
18	Preset1_IN	Preset value 1	gray/brown
19	I_Latch	High=Latch	white/pink
20	Direction IN	Change of counting direction	pink/brown
21	Preset2_IN	Preset value 2	white/blue
22	Ser.Program+_IN/OUT	Ser. programming interface RS485	brown/blue
23	Ser.Program-_IN/OUT	Ser. programming interface RS485	white/red
24	Supply Voltage IN	Supply voltage	brown/red
25	Ground IN	Ground	white/black

WARNING

'De-energize the system before carrying out wiring work or opening and closing electrical connections !

Short-circuits, voltage peaks, etc. can cause operating failures and uncontrolled operating states, as well as serious personal injuries and damage to property.

Verdrahtungsarbeiten, Öffnen und Schließen von elektrischen Verbindungen nur im spannungslosen Zustand durchführen ! Kurzschlüsse, Spannungsspitzen etc. können zur Fehlfunktion und unkontrollierten Zuständen der Anlage bzw. zu erheblichen Personen- und Sachschäden führen.