

## Pin assignment

Pin assignment number: 3394

Index:

13.01.2021

Connector name: 16-pol CONTACT

Pin-count: 16

Page: 1/1

Pin	Designation	Description	Colour
1	CH_A_OUT	Channel A	-
2	not connected		-
3	CH_B_OUT	Channel B	-
4	not connected		-
5	not connected		-
6	not connected		-
7	Ser.Program+_IN/OUT	Ser. programming interface RS485	-
8	Ser.Program-_IN/OUT	Ser. programming interface RS485	-
9	not connected		-
10	not connected		-
11	Preset1_IN	Preset value 1	-
12	Direction IN	Change of counting direction	-
13	not connected		-
14	not connected		-
15	Supply Voltage IN	Supply voltage	-
16	Ground IN	Ground	-

### WARNING

'De-energize the system before carrying out wiring work or opening and closing electrical connections !

Short-circuits, voltage peaks, etc. can cause operating failures and uncontrolled operating states, as well as serious personal injuries and damage to property.

Verdrahtungsarbeiten, Öffnen und Schließen von elektrischen Verbindungen nur im spannungslosen Zustand durchführen ! Kurzschlüsse, Spannungsspitzen etc. können zur Fehlfunktion und unkontrollierten Zuständen der Anlage bzw. zu erheblichen Personen- und Sachschäden führen.