

## Pin assignment

Pin assignment number: 3481

Connector name: 15-pol SUB-D

Index:

Pin-count: 15

13.01.2021

Page: 1/1

Pin	Designation	Description	Colour
1	/CH_A_OUT	Channel A inverted	-
2	CH_A_OUT	Channel A	-
3	CH_B_OUT	Channel B	-
4	/CH_B_OUT	Channel B inverted	-
5	not connected		-
6	not connected		-
7	not connected		-
8	not connected		-
9	SSI_DATA-_OUT	Data output -	-
10	SSI_DATA+_OUT	Data output +	-
11	SSI_Clock-_IN	Clock input -	-
12	SSI_Clock+_IN	Clock input +	-
13	Ground IN	Ground	-
14	not connected		-
15	Supply Voltage IN	Supply voltage	-

### WARNING

'De-energize the system before carrying out wiring work or opening and closing electrical connections !

Short-circuits, voltage peaks, etc. can cause operating failures and uncontrolled operating states, as well as serious personal injuries and damage to property.

Verdrahtungsarbeiten, Öffnen und Schließen von elektrischen Verbindungen nur im spannungslosen Zustand durchführen ! Kurzschlüsse, Spannungsspitzen etc. können zur Fehlfunktion und unkontrollierten Zuständen der Anlage bzw. zu erheblichen Personen- und Sachschäden führen.