

Pin assignment

Pin assignment number: 3533

Index:

13.01.2021

Connector name: M23 12-pol

Pin-count: 12

Page: 1/1

Pin	Designation	Description	Colour
1	CH_A_OUT	Channel K1.A	-
2	CH_A_OUT	Channel K2.A	-
3	CH_B_OUT	Channel K1.B	-
4	CH_B_OUT	Channel K2.B	-
5	Ser.Program+_IN/OUT	Ser. programming interface RS485	-
6	CH_C_OUT	Channel K1.C	-
7	CH_D_OUT	Channel K1.D	-
8	Ser.Program-_IN/OUT	Ser. programming interface RS485	-
9	Overspeed_OUT	Overspeed	-
10	Ground IN	Ground	-
11	not connected		-
12	Critical frequency 100kHz	Default 200kHz	-

WARNING

'De-energize the system before carrying out wiring work or opening and closing electrical connections !

Short-circuits, voltage peaks, etc. can cause operating failures and uncontrolled operating states, as well as serious personal injuries and damage to property.

Verdrahtungsarbeiten, Öffnen und Schließen von elektrischen Verbindungen nur im spannungslosen Zustand durchführen ! Kurzschlüsse, Spannungsspitzen etc. können zur Fehlfunktion und unkontrollierten Zuständen der Anlage bzw. zu erheblichen Personen- und Sachschäden führen.