

Pin assignment

Pin assignment number: 3662

Index:

13.01.2021

Connector name: with cable outlet

Pin-count: 10

Page: 1/1

Pin	Designation	Description	Colour
1	Analog_OUT	Analog output	gray
2	not connected		
3	not connected		
4	not connected		
5	Ser.Program+_IN/OUT	Ser. programming interface RS485	green
6	Ser.Program-_IN/OUT	Ser. programming interface RS485	yellow
7	Ground IN	Ground	black+white
8	Supply Voltage IN	Supply voltage	red+pink
9	not connected		
10	not connected		

Supply voltage 'USS R in series with Analog_OUT

10-17V 330 ohm

18-25V 560 ohm

26-33V 860 ohm

WARNING

'De-energize the system before carrying out wiring work or opening and closing electrical connections !

Short-circuits, voltage peaks, etc. can cause operating failures and uncontrolled operating states, as well as serious personal injuries and damage to property.

Verdrahtungsarbeiten, Öffnen und Schließen von elektrischen Verbindungen nur im spannungslosen Zustand durchführen ! Kurzschlüsse, Spannungsspitzen etc. können zur Fehlfunktion und unkontrollierten Zuständen der Anlage bzw. zu erheblichen Personen- und Sachschäden führen.