

## Pin assignment

Pin assignment number: 3679

Index:

13.01.2021

Connector name: with cable outlet

Pin-count: 25

Page: 1/1

Pin	Designation	Description	Colour
1	CH_A_OUT	Channel A	white
2	not connected		
3	CH_B_OUT	Channel B	green
4	not connected		
5	Ser.Program+_IN/OUT	Ser. programming interface RS485	gray
6	Ser.Program-_IN/OUT	Ser. programming interface RS485	pink
7	ISI_Set_IN	Load	blue
8	ISI_Set_Done_OUT	Load End	red
9	Preset1_IN	Preset value 1	black
10	Preset2_IN	Preset value 2	violet
11	Supply Voltage IN	Supply voltage	gray/pink
12	Ground IN	Ground	red/blue
13	not connected		
14	not connected		
15	not connected		
16	not connected		
17	not connected		
18	not connected		
19	not connected		
20	not connected		
21	not connected		
22	not connected		
23	not connected		
24	not connected		
25	not connected		

### WARNING

'De-energize the system before carrying out wiring work or opening and closing electrical connections !

Short-circuits, voltage peaks, etc. can cause operating failures and uncontrolled operating states, as well as serious personal injuries and damage to property.

Verdrahtungsarbeiten, Öffnen und Schließen von elektrischen Verbindungen nur im spannungslosen Zustand durchführen ! Kurzschlüsse, Spannungsspitzen etc. können zur Fehlfunktion und unkontrollierten Zuständen der Anlage bzw. zu erheblichen Personen- und Sachschäden führen.