

## Pin assignment

Pin assignment number: 3790

Index:

13.01.2021

Connector name: 12-pol M12-Connector

Pin-count: 12

Page: 1/1

Pin	Designation	Description	Colour
1	SSI_Clock+_IN	Clock input +	-
2	not connected		-
3	SSI_Clock-_IN	Clock input -	-
4	SSI_DATA+_OUT	Data output +	-
5	Ser.Program-_IN/OUT	Ser. programming interface RS485	-
6	SSI_DATA-_OUT	Data output -	-
7	Preset1_IN	Preset value 1	-
8	Ser.Program+_IN/OUT	Ser. programming interface RS485	-
9	Direction IN	Change of counting direction	-
10	not connected		-
11	Supply Voltage IN	Supply voltage	-
12	Ground IN	Ground	-

### WARNING

'De-energize the system before carrying out wiring work or opening and closing electrical connections !

Short-circuits, voltage peaks, etc. can cause operating failures and uncontrolled operating states, as well as serious personal injuries and damage to property.

Verdrahtungsarbeiten, Öffnen und Schließen von elektrischen Verbindungen nur im spannungslosen Zustand durchführen ! Kurzschlüsse, Spannungsspitzen etc. können zur Fehlfunktion und unkontrollierten Zuständen der Anlage bzw. zu erheblichen Personen- und Sachschäden führen.