

Pin assignment

Pin assignment number: 4041

Index:

13.01.2021

Connector name: 26-pol TELDIX

Pin-count: 26

Page: 1/1

Pin	Designation	Description	Colour
A	CH_A_OUT	Channel A	-
B	/CH_A_OUT	Channel A inverted	-
C	CH_B_OUT	Channel B	-
D	/CH_B_OUT	Channel B inverted	-
E	Ser.Program+_IN/OUT	Ser. programming interface RS485	-
F	Ser.Program-_IN/OUT	Ser. programming interface RS485	-
G	ISI_Set_IN	Load	-
H	ISI_Set_Done_OUT	Load End	-
J	Preset1_IN	Preset value 1	-
K	CH_I_OUT	Channel Reference	-
L	/CH_I_OUT	Channel Reference inverted	-
M	not connected		-
N	not connected		-
P	not connected		-
R	not connected		-
S	not connected		-
T	not connected		-
U	not connected		-
V	not connected		-
W	not connected		-
X	not connected		-
Y	not connected		-
Z	not connected		-
a	Supply Voltage IN	Supply voltage 11-27V	-
b	Ground IN	Ground	-
c	not connected		-

WARNING

'De-energize the system before carrying out wiring work or opening and closing electrical connections !

Short-circuits, voltage peaks, etc. can cause operating failures and uncontrolled operating states, as well as serious personal injuries and damage to property.

Verdrahtungsarbeiten, Öffnen und Schließen von elektrischen Verbindungen nur im spannungslosen Zustand durchführen ! Kurzschlüsse, Spannungsspitzen etc. können zur Fehlfunktion und unkontrollierten Zuständen der Anlage bzw. zu erheblichen Personen- und Sachschäden führen.