

Pin assignment

Pin assignment number: 515

Connector name: 26-pol CONTACT

Index:

Pin-count: 26

13.01.2021

Page: 1/2

| Pin | Designation | Description | Colour |
|-----|-------------------|------------------------------|--------|
| 1 | O_D0 | Data output | - |
| 2 | O_D1 | Data output | - |
| 3 | O_D2 | Data output | - |
| 4 | O_D3 | Data output | - |
| 5 | O_D4 | Data output | - |
| 6 | O_D5 | Data output | - |
| 7 | O_D6 | Data output | - |
| 8 | O_D7 | Data output | - |
| 9 | O_D8 | Data output | - |
| 10 | O_D9 | Data output | - |
| 11 | O_D10 | Data output | - |
| 12 | O_D11 | Data output | - |
| 13 | O_D12 | Data output | - |
| 14 | O_D13 | Data output | - |
| 15 | O_D14 | Data output | - |
| 16 | O_D15 | Data output | - |
| 17 | O_D16 | Data output | - |
| 18 | O_D17 | Data output | - |
| 19 | O_D18 | Data output | - |
| 20 | not connected | | - |
| 21 | Direction IN | Change of counting direction | - |
| 22 | Select-Input S1 | | - |
| 23 | Select-Input S2 | | - |
| 24 | Supply Voltage IN | Supply voltage | - |
| 25 | Ground IN | Ground | - |
| 26 | Preset1_IN | Preset value 1 | - |

Programming inputs: 'S1 S2 Programming

0 0 512/1024

1 0 512/512

0 1 512/256

1 1 128/256

Notice: Inputs must be terminated!

Pin assignment

Pin assignment number: 515

Connector name: 26-pol CONTACT

Index:

Pin-count: 26

13.01.2021

Page: 2/2

WARNING

'De-energize the system before carrying out wiring work or opening and closing electrical connections !

Short-circuits, voltage peaks, etc. can cause operating failures and uncontrolled operating states, as well as serious personal injuries and damage to property.

Verdrahtungsarbeiten, Öffnen und Schließen von elektrischen Verbindungen nur im spannungslosen Zustand durchführen ! Kurzschlüsse, Spannungsspitzen etc. können zur Fehlfunktion und unkontrollierten Zuständen der Anlage bzw. zu erheblichen Personen- und Sachschäden führen.