

## Pin assignment

Pin assignment number: 710

Index:

13.01.2021

Connector name: 39-pol TELDIX

Pin-count: 39

Page: 1/1

Pin	Designation	Description	Colour
A	O_D0	Data output	-
B	O_D1	Data output	-
C	O_D2	Data output	-
D	O_D3	Data output	-
E	O_D4	Data output	-
F	O_D5	Data output	-
G	O_D6	Data output	-
H	O_D7	Data output	-
J	O_D8	Data output	-
K	O_D9	Data output	-
L	O_D10	Data output	-
M	O_D11	Data output	-
N	O_D12	Data output	-
P	O_D13	Data output	-
R	O_D14	Data output	-
S	O_D15	Data output	-
T	O_D16	Data output	-
U	not connected		-
V	not connected		-
W	Direction IN	Counting direction increasing	-
X	Supply Voltage IN	Supply voltage	-
Y	Ground IN	Ground	-
Z	I_Latch	Data latched	-
a	Supply Voltage IN	Supply voltage	-
b	Ground IN	Ground	-
c	Ser.Program+_IN/OUT	Ser. programming interface RS485	-
d	Ser.Program-_IN/OUT	Ser. programming interface RS485	-
e	Preset1_IN	(Preset1)	-
f	not connected		-
g	not connected		-
h	not connected		-
i	not connected		-
j	not connected		-
k	not connected		-
m	not connected		-
n	not connected		-
p	not connected		-
q	not connected		-
r	not connected		-