

Pin assignment

Pin assignment number: 961

Connector name: 32-pol CANNON

Index:

Pin-count: 32

13.01.2021

Page: 1/1

Pin	Designation	Description	Colour
A	O_D0	Data output	-
B	O_D1	Data output	-
C	O_D2	Data output	-
D	O_D3	Data output	-
E	O_D4	Data output	-
F	O_D5	Data output	-
G	O_D6	Data output	-
H	O_D7	Data output	-
J	O_D8	Data output	-
K	O_D9	Data output	-
L	O_D10	Data output	-
M	O_D11	Data output	-
N	O_D12	Data output	-
P	O_D13	Data output	-
R	O_D14	Data output	-
S	O_D15	Data output	-
T	O_D16	Data output	-
U	O_D17	Data output	-
V	O_D18	Data output	-
W	O_D19	Data output	-
X	DataBus_disable_IN	High=tristate	-
Y	I_Latch	High=Latch	-
Z	Preset1_IN	Preset value 1	-
a	Supply Voltage IN	Supply voltage	-
b	Ground IN	Ground	-
c	Program_Enable_IN	High=Progr.-Enable	-
d	not connected		-
e	not connected		-
f	not connected		-
g	not connected		-
h	not connected		-
i	not connected		-