

Pin assignment

Pin assignment number: 9818

Connector name: 15-pol SUB-D

Index:

Pin-count: 15

24.06.2024

Page: 1/1

Pin	Designation	Description	Colour
1	CH_A_OUT	Channel A	-
2	Ground IN	Ground	-
3	CH_B_OUT	Channel B	-
4	Supply Voltage IN	Supply voltage	-
5	not connected		-
6	not connected		-
7	/CH_I_OUT	Channel Reference inverted	-
8	not connected		-
9	/CH_A_OUT	Channel A inverted	-
10	0V sensor	Ground	-
11	/CH_B_OUT	Channel B inverted	-
12	Ub sensor	Supply voltage	-
13	not connected		-
14	CH_I_OUT	Channel Reference	-
15	not connected		-

Shield

'Shield over connector housing

Schirm über Steckergehäuse

,

WARNING

'De-energize the system before carrying out wiring work or opening and closing electrical connections !

Short-circuits, voltage peaks, etc. can cause operating failures and uncontrolled operating states, as well as serious personal injuries and damage to property.

Verdrahtungsarbeiten, Öffnen und Schließen von elektrischen Verbindungen nur im spannungslosen Zustand durchführen ! Kurzschlüsse, Spannungsspitzen etc. können zur Fehlfunktion und unkontrollierten Zuständen der Anlage bzw. zu erheblichen Personen- und Sachschäden führen.

,