

Pin assignment

Pin assignment number: 9982

Index:

13.01.2021

Connector name: 37-pol SUB-D

Pin-count: 37

Page: 1/1

Pin	Designation	Description	Colour
1	Ground IN	Ground	-
2	O_D0	Data output	-
3	O_D2	Data output	-
4	O_D4	Data output	-
5	O_D6	Data output	-
6	O_D8	Data output	-
7	O_D10	Data output	-
8	O_D12	Data output	-
9	O_D14	Data output	-
10	Preset1_IN	Preset value 1	-
11	not connected		-
12	not connected		-
13	Direction IN	Supply voltage	-
14	not connected		-
15	not connected		-
16	not connected		-
17	not connected		-
18	not connected		-
19	not connected		-
20	not connected		-
21	O_D1	Data output	-
22	O_D3	Data output	-
23	O_D5	Data output	-
24	O_D7	Data output	-
25	O_D9	Data output	-
26	O_D11	Data output	-
27	O_D13	Data output	-
28	O_D15	Data output	-
29	not connected		-
30	not connected		-
31	Supply Voltage IN	Supply voltage	-
32	not connected		-
33	not connected		-
34	Ser.Program+_IN/OUT	Ser. programming interface RS485	-
35	Ser.Program-_IN/OUT	Ser. programming interface RS485	-
36	not connected		-
37	not connected		-