

Pin assignment

Pin assignment number: 2699

Index: + 2698 = K201

26.07.2011

Connector name: 12-pol.CONTACT Pin-count: 12

Page: 1/1

Pin	Designation	Description	Level	Driver	NC	Color
1	/CH_B_OUT	Channel B inverted	5V	RS 422		white
2	not connected					
3	CH_I_OUT	Channel Reference	5V	RS 422		green
4	/CH_I_OUT	Channel Reference inverted	5V	RS 422		brown
5	CH_A_OUT	Channel A	5V	RS 422		yellow
6	/CH_A_OUT	Channel A inverted	5V	RS 422		violet
7	not connected					
8	CH_B_OUT	Channel B	5V	RS 422		pink
9	not connected					
10	Ground IN	Ground	0V			blue
11	not connected					
12	Supply Voltage IN	Supply voltage	11-27V			red

Pin assignment

Pin assignment number: 2698

Index: + 2699 = K201

26.07.2011

Connector name: 12-pol.CONTACT Pin-count: 12

Page: 1/1

Pin	Designation	Description	Level	Driver	NC	Color
1	Control IN	750+3 Zero pulse	Supply Voltage		0	
2	Control IN	1000+4 Zero pulse	Supply Voltage		0	
3	Control IN	1250+5 Zero pulse	Supply Voltage		0	
4	not connected					
5	not connected					
6	not connected					
7	not connected					
8	not connected					
9	not connected					
10	not connected					
11	not connected					
12	Ground IN	Ground	0V			

Notice 12p.-Contact :

'!!! 12 pole - CONTACT - Socket !!!