

Pin assignment

Pin assignment number: 2726**Index: + 2727 = K203**

29.08.2011

Connector name: 12-pol.CONTACT Pin-count: 12

Page: 1/1

Pin	Designation	Description	Level	Driver	NC	Color
1	Softendswitch_OUT	Output	11-27V	Push Pull		white
2	Softendswitch_OUT	Output	11-27V	Push Pull		brown
3	Softendswitch_OUT	Output	11-27V	Push Pull		green
4	Softendswitch_OUT	Output	11-27V	Push Pull		yellow
5	Softendswitch_OUT	Output	11-27V	Push Pull		gray
6	Softendswitch_OUT	Output	11-27V	Push Pull		pink
7	Softendswitch_OUT	Output	11-27V	Push Pull		blue
8	Softendswitch_OUT	Output	11-27V	Push Pull		red
9	not connected					
10	not connected					
11	Supply Voltage IN	Supply voltage	11-27V			gray/pink
12	Ground IN	Ground	0V			red/blue

Pin assignment

Pin assignment number: 2727

Index: + 2726 = K203

29.08.2011

Connector name: 17-pol.CONTACT Pin-count: 17

Page: 1/1

Pin	Designation	Description	Level	Driver	NC	Color
1	SSI_Clock-_IN	Clock input -	RS 422	RS 422		white
2	SSI_Clock+_IN	Clock input +	RS 422	RS 422		brown
3	SSI_DATA+_OUT	Data output +	RS 422	RS 422		green
4	SSI_DATA-_OUT	Data output -	RS 422	RS 422		yellow
5	Ser.Program+_IN/OUT	Ser. programming interface RS485	RS 485	RS 485		gray
6	Ser.Program-_IN/OUT	Ser. programming interface RS485	RS 485	RS 485		pink
7	not connected					
8	Direction IN	Counting direction increasing	Supply Voltage		0	red
9	Preset1_IN	Preset value 1	Supply Voltage		0	black
10	Preset2_IN	Preset value 2	Supply Voltage		0	violet
11	not connected					
12	CH_A_OUT	Channel A	RS 422	RS 422		red/blue
13	/CH_A_OUT	Channel A inverted	RS 422	RS 422		withe/green
14	CH_B_OUT	Channel B	RS 422	RS 422		brown/green
15	/CH_B_OUT	Channel B inverted	RS 422	RS 422		withe/yellow
16	Supply Voltage IN	Supply voltage	11-27V			yellow/brown
17	Ground IN	Ground	0V			withe/gray