

Pin assignment

Pin assignment number: 2528

Index: + 2529 = K207

29.08.2011

Connector name: 9-pol.CONTACT Pin-count: 9

Page: 1/1

Pin	Designation	Description	Level	Driver	NC	Color
1	IBS_DO2_OUT	Data output Remote OUT	RS 422	RS 422		white
2	IBS_DO2_OUT	Data output Remote OUT	RS 422	RS 422		brown
3	IBS_DI2_IN	Data input Remote OUT	RS 422	RS 422		green
4	IBS_DI2_IN	Data input Remote OUT	RS 422	RS 422		yellow
5	IBS_Ground2	Ground galvanically isolated	0V			gray
6	not connected					
7	Supply Voltage IN	Supply voltage	11-27V			blue
8	Ground IN	Ground	0V			red
9	IBS_RBST_IN	Remote Bus Connector				black

REMOTE OUT : (9 pole Socket)

,

Pin assignment

Pin assignment number: 2529

Index: + 2528 = K207

29.08.2011

Connector name: 9-pol.CONTACT Pin-count: 9

Page: 1/1

Pin	Designation	Description	Level	Driver	NC	Color
1	IBS_DO1_OUT	Data output Remote IN	RS 422	RS 422		white
2	IBS_DO1_OUT	Data output Remote IN	RS 422	RS 422		brown
3	IBS_DI1_IN	Data input Remote IN	RS 422	RS 422		green
4	IBS_DI1_IN	Data input Remote IN	RS 422	RS 422		yellow
5	IBS_Ground1	Ground galvanically isolated	0V			gray
6	not connected					
7	Supply Voltage IN	Supply voltage	11-27V			blue
8	Ground IN	Ground	0V			red
9	not connected					

REMOTE IN : (9 pole Plug)

,