

Pin assignment

Pin assignment number: 459
Index:

30.08.2011

Connector name: 25-pol.SUB-D
Pin-count: 25
+ 2769 + 2760 = K208

Page: 1/1

Pin	Designation	Description	Level	Driver	NCC	Color
1	O_D0	Data output				
2	O_D1	Data output				
3	O_D2	Data output				
4	O_D3	Data output				
5	O_D4	Data output				
6	O_D5	Data output				
7	O_D6	Data output				
8	O_D7	Data output				
9	O_D8	Data output				
10	O_D9	Data output				
11	O_D10	Data output				
12	O_D11	Data output				
13	O_D12	Data output				
14	O_D13	Data output				
15	O_D14	Data output				
16	O_D15	Data output				
17	O_D16	Data output				
18	O_D17	Data output				
19	I_Latch	High=Latch	> 8 Volt			
20	Preset1_IN	Preset value 1	> 8 Volt			
21	Direction IN	Change of counting direction	> 8 Volt			
22	Ser.Program+_IN/OUT	Ser. programming interface RS485	5V	RS 485		
23	Ser.Program-_IN/OUT	Ser. programming interface RS485	5V	RS 485		
24	Supply Voltage IN	Supply voltage	19..27V			
25	Ground IN	Ground	0V			

WARNING !!

'De-energize the system before carrying out wiring work or opening and closing electrical connections !!!

Short-circuits, voltage peaks, etc. can cause operating failures and uncontrolled operating states, as well as serious personal injuries and damage to property.

Verdrahtungsarbeiten, Öffnen und Schließen von elektrischen Verbindungen nur im spannungslosen Zustand durchführen !!! Kurzschlüsse, Spannungsspitzen etc. können zur Fehlfunktion und unkontrollierten Zuständen der Anlage bzw. zu erheblichen Personen- und Sachschäden führen.

Pin assignment

Pin assignment number: 2769**Index:**

30.08.2011

Connector name: 4-pol.HARTING**Pin-count: 4****+ 2760 + 459 = K208**

Page: 1/1

Pin	Designation	Description	Level	Driver	NC	Color
1	Supply Voltage IN	Supply voltage	19..27V			brown/red
2	Ground IN	Ground	0V			withe/black
3	not connected					
4	not connected					

Pin assignment

Pin assignment number: 2760

Index:

30.08.2011

Connector name: 26-pol.TELDIX

Pin-count: 26

+ 2769 + 459 = K208

Page: 1/1

Pin	Designation	Description	Level	Driver	NC	Color
A	O_D0	Data output				white
B	O_D1	Data output				brown
C	O_D2	Data output				green
D	O_D3	Data output				yellow
E	O_D4	Data output				gray
F	O_D5	Data output				pink
G	O_D6	Data output				blue
H	O_D7	Data output				red
J	O_D8	Data output				black
K	O_D9	Data output				violet
L	O_D10	Data output				gray/pink
M	O_D11	Data output				red/blue
N	O_D12	Data output				withe/green
P	O_D13	Data output				brown/green
R	O_D14	Data output				withe/yellow
S	O_D15	Data output				yellow/brown
T	O_D16	Data output				withe/gray
U	O_D17	Data output				gray/brown
V	not connected					
W	not connected					
X	not connected					
Y	not connected					
Z	not connected					
a	not connected					
b	not connected					
c	not connected					