

Pin assignment

Pin assignment number: 2635

Index: A + 246 = K286

05.09.2011

Connector name: 26-pol.TELDIX

Pin-count: 26

Page: 1/1

| Pin | Designation | Description | Level | Driver | NC | Color |
|-----|-------------------|----------------|----------------|--------|----|--------------|
| A | O_D0 | Data output | | | | white |
| B | O_D1 | Data output | | | | brown |
| C | O_D2 | Data output | | | | green |
| D | O_D3 | Data output | | | | yellow |
| E | O_D4 | Data output | | | | gray |
| F | O_D5 | Data output | | | | pink |
| G | O_D6 | Data output | | | | blue |
| H | O_D7 | Data output | | | | red |
| J | O_D8 | Data output | | | | black |
| K | O_D9 | Data output | | | | violet |
| L | O_D10 | Data output | | | | gray/pink |
| M | O_D11 | Data output | | | | red/blue |
| N | O_D12 | Data output | | | | withe/green |
| P | O_D13 | Data output | | | | brown/green |
| R | O_D14 | Data output | | | | withe/yellow |
| S | O_D15 | Data output | | | | yellow/brown |
| T | O_D16 | Data output | | | | withe/gray |
| U | O_D17 | Data output | | | | gray/brown |
| V | O_D18 | Data output | | | | withe/pink |
| W | O_D19 | Data output | | | | pink/brown |
| X | O_D20 | Data output | | | | withe/blue |
| Y | I_Latch | High=Latch | Supply Voltage | | 0 | brown/blue |
| Z | Preset1_IN | Preset value 1 | Supply Voltage | | 0 | withe/red |
| a | not connected | | | | | |
| b | Supply Voltage IN | Supply voltage | 11-27V | | | withe/black |
| c | Ground IN | Ground | 0V | | | brown/black |

WARNING !!

'De-energize the system before carrying out wiring work or opening and closing electrical connections !!!

Short-circuits, voltage peaks, etc. can cause operating failures and uncontrolled operating states, as well as serious personal injuries and damage to property.

Verdrahtungsarbeiten, Öffnen und Schließen von elektrischen Verbindungen nur im spannungslosen Zustand durchführen !!! Kurzschlüsse, Spannungsspitzen etc. können zur Fehlfunktion und unkontrollierten Zuständen der Anlage bzw. zu erheblichen Personen- und Sachschäden führen.

Pin assignment

Pin assignment number: 246

Index: + 2635A = K286

31.08.2011

Connector name: 15-pol.SUB-D

Pin-count: 15

Page: 1/1

| Pin | Designation | Description | Level | Driver | NC | Color |
|-----|---------------------|----------------------------------|--------|--------|----|--------------|
| 1 | Ser.Program-_IN/OUT | Ser. programming interface RS485 | RS 485 | RS 485 | | white |
| 2 | Ser.Program+_IN/OUT | Ser. programming interface RS485 | RS 485 | RS 485 | | brown |
| 3 | not connected | | | | | |
| 4 | not connected | | | | | |
| 5 | not connected | | | | | |
| 6 | not connected | | | | | |
| 7 | not connected | | | | | |
| 8 | not connected | | | | | |
| 9 | not connected | | | | | |
| 10 | not connected | | | | | |
| 11 | not connected | | | | | |
| 12 | not connected | | | | | |
| 13 | not connected | | | | | |
| 14 | Supply Voltage IN | Supply voltage | 11-27V | | | brown/green |
| 15 | Ground IN | Ground | 0V | | | withe/yellow |

WARNING !!

'De-energize the system before carrying out wiring work or opening and closing electrical connections !!!

Short-circuits, voltage peaks, etc. can cause operating failures and uncontrolled operating states, as well as serious personal injuries and damage to property.

Verdrahtungsarbeiten, Öffnen und Schließen von elektrischen Verbindungen nur im spannungslosen Zustand durchführen !!! Kurzschlüsse, Spannungsspitzen etc. können zur Fehlfunktion und unkontrollierten Zuständen der Anlage bzw. zu erheblichen Personen- und Sachschäden führen.