

Pin assignment

Pin assignment number: 3248

Index: + 2523 = K337

13.09.2011

Connector name: 12-pol.CONTACT

Pin-count: 12

Page: 1/1

Pin	Designation	Description	Level	Driver	NC	Colour
1	CH_A_OUT	Channel A	11-27V	Push Pull		white
2	not connected					
3	not connected					
4	CH_B_OUT	Channel B	11-27V	Push Pull		yellow
5	not connected					
6	not connected					
7	CH_I_OUT	Channel Reference	11-27V	Push Pull		blue
8	Preset K0_IN		Supply Voltage		0	red
9	Ser.Program+_IN/OUT	Ser. programming interface RS485	RS 485	RS 485		black
10	Ser.Program-_IN/OUT	Ser. programming interface RS485	RS 485	RS 485		violet
11	Supply Voltage IN	Supply voltage	11-27V			gray/pink
12	Ground IN	Ground	0V			red/blue

WARNING !!

'De-energize the system before carrying out wiring work or opening and closing electrical connections !!!
Short-circuits, voltage peaks, etc. can cause operating failures and uncontrolled operating states, as well as serious personal injuries and damage to property.

Verdrahtungsarbeiten, Öffnen und Schließen von elektrischen Verbindungen nur im spannungslosen Zustand durchführen !!! Kurzschlüsse, Spannungsspitzen etc. können zur Fehlfunktion und unkontrollierten Zuständen der Anlage bzw. zu erheblichen Personen- und Sachschäden führen.

Pin assignment

Pin assignment number: 2523

Index: + 3248 = K337

13.09.2011

Connector name: 12-pol.CONTACT

Pin-count: 12

Page: 1/1

Pin	Designation	Description	Level	Driver	NC	Colour
1	Heating_IN	Heating +24V				white 0,5
2	Heating_Ground_IN	Heating Ground				brown 0,5
3	not connected					
4	not connected					
5	Heating_Ground_IN	Heating Ground				brown 0,5
6	not connected					
7	not connected					
8	not connected					
9	Heating_IN	Heating +24V				white 0,5
10	not connected					
11	not connected					
12	not connected					

Connector coding

'!!! Connector Y - coded !!!
