

# Pin assignment

Pin assignment number: 9722

Index: + 246 = K402

11.07.2011

Connector name: 25-pol.SUB-D

Pin-count: 25

Page: 1/1

Pin	Designation	Description	Level	Driver	NC	Color
1	O_D0	Data output				white
2	O_D1	Data output				brown
3	O_D2	Data output				green
4	O_D3	Data output				yellow
5	O_D4	Data output				gray
6	O_D5	Data output				pink
7	O_D6	Data output				blue
8	O_D7	Data output				red
9	O_D8	Data output				black
10	O_D9	Data output				violet
11	O_D10	Data output				gray/pink
12	O_D11	Data output				red/blue
13	O_D12	Data output				withe/green
14	O_D13	Data output				brown/green
15	O_D14	Data output				withe/yellow
16	O_D15	Data output				yellow/brown
17	O_D16	Data output				withe/gray
18	O_D17	Data output				gray/brown
19	O_D18	Data output				withe/pink
20	O_D19	Data output				pink/brown
21	O_D20	Data output				withe/blue
22	not connected					brown/blue
23	Preset1_IN	Preset value 1	Supply Voltage		0	withe/red
24	Supply Voltage IN	Supply voltage	11-27V			brown/red
25	Ground IN	Ground	0V			withe/black

**WARNING !!**

**'De-energize the system before carrying out wiring work or opening and closing electrical connections !!!**

**Short-circuits, voltage peaks, etc. can cause operating failures and uncontrolled operating states, as well as serious personal injuries and damage to property.**

**Verdrahtungsarbeiten, Öffnen und Schließen von elektrischen Verbindungen nur im spannungslosen Zustand durchführen !!! Kurzschlüsse, Spannungsspitzen etc. können zur Fehlfunktion und unkontrollierten Zuständen der Anlage bzw. zu erheblichen Personen- und Sachschäden führen.**

# Pin assignment

Pin assignment number: 246

Index: + 9722 = K402

11.07.2011

Connector name: 15-pol.SUB-D

Pin-count: 15

Page: 1/1

Pin	Designation	Description	Level	Driver	NC	Color
1	Adress 2 <sup>0</sup> _IN	Encoder address 2 <sup>0</sup>	Supply Voltage		0	white
2	Adress 2 <sup>1</sup> _IN	Encoder address 2 <sup>1</sup>	Supply Voltage		0	brown
3	Adress 2 <sup>2</sup> _IN	Encoder address 2 <sup>2</sup>	Supply Voltage		0	green
4	Adress 2 <sup>3</sup> _IN	Encoder address 2 <sup>3</sup>	Supply Voltage		0	yellow
5	not connected					
6	DATA+_OUT	Data output +	RS 422	RS 422		pink
7	DATA-_OUT	Data output -	RS 422	RS 422		blue
8	Clock+_IN	Clock input +	RS 422	RS 422		red
9	Clock-_IN	Clock input -	RS 422	RS 422		black
10	not connected					
11	not connected					
12	Format recognition					red/blue
13	not connected					
14	Supply Voltage IN	Supply voltage	11-27V			brown/green
15	Ground IN	Data output	0V			withe/yellow

**FORMAT DETECTION:**

'LOW = TA-MINI

HIGH = PT-100

**WARNING !!**

'De-energize the system before carrying out wiring work or opening and closing electrical connections !!!

Short-circuits, voltage peaks, etc. can cause operating failures and uncontrolled operating states, as well as serious personal injuries and damage to property.

Verdrahtungsarbeiten, Öffnen und Schließen von elektrischen Verbindungen nur im spannungslosen Zustand durchführen !!! Kurzschlüsse, Spannungsspitzen etc. können zur Fehlfunktion und unkontrollierten Zuständen der Anlage bzw. zu erheblichen Personen- und Sachschäden führen.