

Pin assignment

Pin assignment number: 662

Index: + 679 = K64

11.07.2011

Connector name: 15-pol.SUB-D

Pin-count: 15

Page: 1/1

Pin	Designation	Description	Level	Driver	NC	Color
1	Ser.Program-_IN/OUT	Ser. programming interface RS485	RS 485	RS 485		white
2	Ser.Program+_IN/OUT	Ser. programming interface RS485	RS 485	RS 485		brown
3	not connected					
4	not connected					
5	not connected					
6	not connected					
7	not connected					
8	not connected					
9	not connected					
10	not connected					
11	not connected					
12	not connected					
13	not connected					
14	Supply Voltage IN	Supply voltage	11-27V			brown/green
15	Ground IN	Data output	0V			withe/yellow

WARNING !!

'De-energize the system before carrying out wiring work or opening and closing electrical connections !!!

Short-circuits, voltage peaks, etc. can cause operating failures and uncontrolled operating states, as well as serious personal injuries and damage to property.

Verdrahtungsarbeiten, Öffnen und Schließen von elektrischen Verbindungen nur im spannungslosen Zustand durchführen !!! Kurzschlüsse, Spannungsspitzen etc. können zur Fehlfunktion und unkontrollierten Zuständen der Anlage bzw. zu erheblichen Personen- und Sachschäden führen.

Pin assignment

Pin assignment number: 679

Index: + 662 = K64

11.07.2011

Connector name: 25-pol.SUB-D

Pin-count: 25

Page: 1/1

Pin	Designation	Description	Level	Driver	NC	Color
1	Preset1_IN	Preset value 1	Supply Voltage		0	white
2	Direction IN	Change of counting direction	Supply Voltage		0	brown
3	Test_Data_IN					green
4	O_D12	Data output				yellow
5	O_D13	Data output				gray
6	O_D14	Data output				pink
7	O_D15	Data output				blue
8	O_D16	Data output				red
9	O_D17	Data output				black
10	not connected					
11	Supply Voltage IN	Supply voltage	11-27V			gray/pink
12	Ground IN	Ground	0V			red/blue
13	Screen	Shield				withe/green
14	O_D0	Data output				brown/green
15	O_D1	Data output				withe/yellow
16	O_D2	Data output				yellow/brown
17	O_D3	Data output				withe/gray
18	O_D4	Data output				gray/brown
19	O_D5	Data output				withe/pink
20	O_D6	Data output				pink/brown
21	O_D7	Data output				withe/blue
22	O_D8	Data output				brown/blue
23	O_D9	Data output				withe/red
24	O_D10	Data output				brown/red
25	O_D11	Data output				withe/black

WARNING !!

'De-energize the system before carrying out wiring work or opening and closing electrical connections !!!

Short-circuits, voltage peaks, etc. can cause operating failures and uncontrolled operating states, as well as serious personal injuries and damage to property.

Verdrahtungsarbeiten, Öffnen und Schließen von elektrischen Verbindungen nur im spannungslosen Zustand durchführen !!! Kurzschlüsse, Spannungsspitzen etc. können zur Fehlfunktion und unkontrollierten Zuständen der Anlage bzw. zu erheblichen Personen- und Sachschäden führen.