

# Pin assignment

Pin assignment number: 703

Index:

26.05.2011

Connector name: 12-pol.CONTACT Pin-count: 12

Page: 1/1

Pin	Designation	Description	Level	Driver	NC	Color
1	SSI_Clock-_IN	Clock input -	5V	RS 422		
2	SSI_Clock+_IN	Clock input +	5V	RS 422		
3	SSI_DATA+_OUT	Data output +	5V	RS 422		
4	SSI_DATA-_OUT	Data output -	5V	RS 422		
5	Ser.Program+_IN/OUT	Ser. programming interface RS485	5V	RS 485		
6	Ser.Program-_IN/OUT	Ser. programming interface RS485	5V	RS 485		
7	not connected					
8	Direction IN	Change of counting direction	Supply Voltage		0	
9	Preset1_IN	Preset value 1	Supply Voltage		0	
10	not connected					
11	Supply Voltage IN	Supply voltage	19..27V			
12	Ground IN	Ground	0V			

**WARNING !!**

'De-energize the system before carrying out wiring work or opening and closing electrical connections !!!  
Short-circuits, voltage peaks, etc. can cause operating failures and uncontrolled operating states, as well as serious personal injuries and damage to property.

Verdrahtungsarbeiten, Öffnen und Schließen von elektrischen Verbindungen nur im spannungslosen Zustand durchführen !!! Kurzschlüsse, Spannungsspitzen etc. können zur Fehlfunktion und unkontrollierten Zuständen der Anlage bzw. zu erheblichen Personen- und Sachschäden führen.

**NOTICE :**

'In case of changing of the counting direction, a Preset adjustment must be performed.