

# Vorkonfektionierte Leitungen: Ethernet



Produktbild	Produktinformation	Länge	Material-Nr. TR
	Kabelstecker M12, 4-polig, D-kodiert, gerade mit offenem Kabelende (geschirmt)	02 m	680-00001
		05 m	680-00002
		10 m	680-00003
		15 m	680-00004
	Kabelstecker M12, 4-polig, D-kodiert, gerade auf Kabelstecker M12, 4-polig, D-kodiert, gerade (geschirmt)	02 m	680-00005
		05 m	680-00006
		10 m	680-00007
		15 m	680-00008
	Kabelstecker M12, 4-polig, D-kodiert, gerade auf RJ45 (geschirmt)	02 m	680-00009
		05 m	680-00010
		10 m	680-00011
		15 m	680-00012
	Kabelstecker M12, 4-polig, D-kodiert, 90° gewinkelt mit offenem Kabelende (geschirmt)	02 m	680-00013
		05 m	680-00014
		10 m	680-00015
		15 m	680-00016
	Kabelstecker M12, 4-polig, D-kodiert, 90° gewinkelt auf Kabelstecker M12, 4-polig, D-Kodiert, 90° gewinkelt (geschirmt)	02 m	680-00017
		05 m	680-00018
		10 m	680-00019
		15 m	680-00020
	Kabelstecker M12, 4-polig, D-kodiert, 90° gewinkelt auf RJ45 (geschirmt)	02 m	680-00021
		05 m	680-00022
		10 m	680-00023
		15 m	680-00024

## Versorgung

	Kabeldose M12, 4-polig, A-kodiert, gerade mit offenem Kabelende (ungeschirmt)	02 m	680-00025
		05 m	680-00026
		10 m	680-00027
		15 m	680-00028
	Kabeldose M12, 4-polig, A-kodiert, 90° gewinkelt mit offenem Kabelende (ungeschirmt)	02 m	680-00029
		05 m	680-00030
		10 m	680-00031
		15 m	680-00032
	Kabeldose M12, 4-polig, A-kodiert, gerade mit offenem Kabelende (geschirmt)	02 m	680-00033
		05 m	680-00034
		10 m	680-00035
		15 m	680-00036
	Kabeldose M12, 4-polig, A-kodiert, 90° gewinkelt mit offenem Kabelende (geschirmt)	02 m	680-00037
		05 m	680-00038
		10 m	680-00039
		15 m	680-00040

Letzte Aktualisierung: 07/2021 · TR-E-TL-DGB-0173-02 · Änderungen in Technik und Design vorbehalten.

## Pre-assembled cable: Ethernet



Product image	Product information	Length	Order code
	Male connector M12, 4-pole, D-coded, straight with open cable end (shielded)	02 m	680-00001
		05 m	680-00002
		10 m	680-00003
		15 m	680-00004
	Male connector M12, 4-pole, D-coded, straight to male connector M12, 4-pole, D-coded, straight (shielded)	02 m	680-00005
		05 m	680-00006
		10 m	680-00007
		15 m	680-00008
	Male connector M12, 4-pole, D-coded, straight to RJ45 (shielded)	02 m	680-00009
		05 m	680-00010
		10 m	680-00011
		15 m	680-00012
	Male connector M12, 4-pole, D-coded, 90° angled with open cable end (shielded)	02 m	680-00013
		05 m	680-00014
		10 m	680-00015
		15 m	680-00016
	Male connector M12, 4-pole, D-coded, 90° angled to male connector M12, 4-pole, D-coded, 90° angled (shielded)	02 m	680-00017
		05 m	680-00018
		10 m	680-00019
		15 m	680-00020
	Male connector M12, 4-pole, D-coded, 90° angled to RJ45 (shielded)	02 m	680-00021
		05 m	680-00022
		10 m	680-00023
		15 m	680-00024

## Supply

	Female connector M12, 4-pole, A-coded, straight with open cable end (unshielded)	02 m	680-00025
		05 m	680-00026
		10 m	680-00027
		15 m	680-00028
	Female connector M12, 4-pole, A-coded, 90° angled with open cable end (unshielded)	02 m	680-00029
		05 m	680-00030
		10 m	680-00031
		15 m	680-00032
	Female connector M12, 4-pole, A-coded, straight with open cable end (shielded)	02 m	680-00033
		05 m	680-00034
		10 m	680-00035
		15 m	680-00036
	Female connector M12, 4-pole, A-coded, 90° angled with open cable end (shielded)	02 m	680-00037
		05 m	680-00038
		10 m	680-00039
		15 m	680-00040

Last update: 07/2021 · TR-E-TI-DGB-0173-02 · Subject to technology and design modifications.